



ME 3000SP

3KW AC

Coupled energy storage inverter



A variety of work modes are optional



LCD+LED – human friendly-machine interface



Outdoor IP65 design



Smart battery energy management system



Compatible with other brands of inverter



Flexible configuration of lead acid or lithium battery



Integrated fanless self-recognition heat dissipation design

Datasheet

ME 3000SP

Battery Parameters

Battery Type	Lithium-ion, Lead-acid
Nominal battery voltage	48V
Battery voltage range	42-58V
Recommended battery capacity	200Ah (100~500Ah optional)
Recommended storage capacity	9.6kWh
Max. Charging current	60A
Charging current range	0-60A (Programmable)
Charging curve	3-Stage adaptive with maintenance
Max. Discharging current	60A
Electronic protection	OCP OTP OVP
Short circuit protection	Fuse (100A)
Discharge times (Hour)	Po=1kVA9.6h Po=3kVA3.2h
Depth of discharge	Lithium-ion: 0-80% DOD adjustable Lead-acid: 0-50% DOD adjustable

AC Parameters

Max. Output power	3kVA
Rated Input/ Output voltage	230V
Max. Input/ Output current	13A
AC Input/ Voltage range	180V-270V
Grid frequency range	44~55Hz / 54~66Hz
THD	< 3%
Power factor	1 default (+/-0.8 adjustable)
Connection phase	Single
Current (inrush)	0.8A/ 1us
Maximum output fault current	100A/ 1us
Maximum output over current protection	13A

System Parameters

Max. Charging efficiency	> 95%
Max. Discharging efficiency	> 95%
Standby losses	< 5W
Topology	High frequency isolated transformer
Degree of protection	IP65
Safety protection	Anti islanding, RCMU, Ground fault monitoring
Communication	RS485, Wifi/Ethernet/GPRS, CAN2.0
SPD protection	III

Environmental

Ambient temperature range	-25°C~ +60°C (Above 45°C Derating)
Allowable relative humidity range	0~ 100%
Protective class	Class I
Max. Operating altitude	2000m
Current sensor connection	External

Emergency Power Supply

EPS rated power	3000VA
EPS rated voltage, Frequency	230V, 50/60Hz
EPS rated current	13A
Total harmonic distortion	< 3%
Switch time	< 3s

General Data

Noise	< 25dB
Weight	16kg
Cooling	Natural
Dimension (W*H*D)	530*360*173mm
Display	LCD display
Warranty	5 Years (Optional: Extension to 10 years)

Standard

EMC	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4
Safety standards	IEC62109-1/2, IEC62040-1
Grid standards	AS/NZS 4777, AS/NZS 62040, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21, EN50549, G83/G98, UTE C15-712-I